

# JV200 Series



Eco-solvent entry-level inkjet printer

54"

64"

## Wide format outdoor printing at an affordable price

High value in a small footprint, the JV200 provides indoor and outdoor durable printing with a proven 330 printhead, easy-to-use software, and a 3-year peace-of-mind warranty. The perfect entry-level printer.

- Easily produce indoor and outdoor prints on a large selection of media with this outstanding entry-level workhorse.
- Enjoy outstanding quality and productivity, plus the industry's best outdoor durability at an attractive price point.
- The ideal vehicle wrap printer for the money on the market.
- Print a wide range of applications using this complete system that includes software, and a range of ink types, and bulk ink options.
- Easy to use with paired RIP software with complete profiles for all standard media types.
- Outstanding quality and productivity at an attractive price point.
- 3-Year warranty is best in the industry
- Mimaki Core Technologies deliver exceptional results, economically, and with maximum productivity.
- Select from two model widths to suit your production needs.

*For best results, always use Mimaki original inks.*

# Mimaki® JV200 Series

|                                   |                                                                                                                                                      |                    |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| <b>Printhead</b>                  | On-demand piezo print head (single)                                                                                                                  |                    |
| <b>Print resolution</b>           | X: 600, 1200 dpi   Y: 600, 900, 1200 dpi                                                                                                             |                    |
| <b>Print speed (4 color mode)</b> | 183 sqft/hr (17 sqm/hr)                                                                                                                              |                    |
|                                   | <b>JV200-130</b>                                                                                                                                     | <b>JV200-160</b>   |
| <b>Maximum print width</b>        | 53.6 in (1361 mm)                                                                                                                                    | 63.4 in (1610 mm)  |
| <b>Maximum media width</b>        | 53.9 in (1371 mm)                                                                                                                                    | 63.8 in (1620 mm)  |
| <b>Weight (uncrated)</b>          | 284.4 lbs (129 kg)                                                                                                                                   | 297.6 lbs (135 kg) |
| <b>Ink Type/Color</b>             | Eco-Solvent inks                                                                                                                                     |                    |
|                                   | SS22 (C, M, Y, K, Lc, Lm, Lk, Or)                                                                                                                    |                    |
| <b>Ink Package Size</b>           | 440ml Cartridges                                                                                                                                     |                    |
|                                   | 1L Bulk Ink Package (for use with optional Mimaki Bulk Ink System)                                                                                   |                    |
| <b>Media Thickness</b>            | up to 0.04 in (1 mm) Printing Gap: manual, two settings (1.5, 2.0 mm)                                                                                |                    |
| <b>Media Weight</b>               | 55 lbs. (25 kg) (with option)                                                                                                                        |                    |
| <b>Certifications</b>             | VCCI class A, FCC class A, ETL IEC 62368-1, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH, Energy Star, RCM, EAC, KC, UKCA |                    |
| <b>Interface</b>                  | USB 2.0 Hi-speed   Ethernet 1000 BASE-T                                                                                                              |                    |
| <b>Power Supply</b>               | AC (100-120V / 200-240V±10%) × two 50/60Hz±1Hz                                                                                                       |                    |
| <b>Power Consumption</b>          | Max. 1320W x2   Sleep mode: 4.5W                                                                                                                     |                    |
| <b>Operational Environment</b>    | Temperature: 68–86 °F ( 20–30 °C)                                                                                                                    |                    |
|                                   | Humidity: 35–65%                                                                                                                                     |                    |
| <b>Dimensions (W x D x H)</b>     | JV200-130: 99 in W x 29.5 in D x 54 in H (2520 mm W x 748 mm D x 1370 mm H)                                                                          |                    |
|                                   | JV200-160: 109 in W x 29.5 in D x 54 in H (2770 mm W x 748 mm D x 1370 mm H)                                                                         |                    |
| <b>Options</b>                    | Mimaki Bulk Ink System, NCU OPT, MBIS BKT OPT                                                                                                        |                    |

Eco-solvent entry-level inkjet printer

54"

64"

Please visit us at: [www.mimakiusa.com](http://www.mimakiusa.com)

Mimaki USA, Inc.  
4851 Thurmon Tanner Parkway, Ste. 100 Flowery Branch GA 30542

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2025, Mimaki USA, Inc.

Rev. 4/11/25